

BGT Materials Limited
2.312 Photon Science Institute
University of Manchester
Oxford Road, Manchester
M13 9PL, United Kingdom
P: +44 (0)161 275 1019
www.bgtmaterials.com
info@bgtmaterials.com

Grat-G1M: High quality graphene powder with predominantly Monolayers

About Grat-G1M[™]


BGT Materials' Grat-G1M products consist of high quality graphene powder, comprising well-exfoliated graphene flakes. Grat-G1M is prepared using our proprietary top-down approach allowing multiple desirable features, including predominantly monolayer flakes, high aspect ratios and low oxygen content. Grat-G1M can be used in a wide range of applications such as transparent conductive coatings, composites and chemical sensors.


Features & benefits

- Predominantly monolayer material.
- Low oxygen content.
- Large lateral dimensions
- Ease of handling and processing.
- Batch-to-batch product consistency.


Technical Specs

Product Analysis	
Appearance	Powder or dispersion (0.1g/L in water or NMP)
Composition	Carbon (> 90.0 %), Oxygen (< 10%)
Flake lateral dimensions	1.15 μm equivalent diameter
Monolayer content	> 95 %






Low magnification scanning electron micrograph showing the morphology of a graphene laminate.



Flakes dropcast from an NMP dispersion on a Si-SiO₂ substrate showing the high yield of monolayer content.



Flake size distribution with an average equivalent diameter of 1.15 μm .

The statement, technical data and recommendations contained herein are based on our investigation and experience, and are believed to be accurate as of the date hereof. In view of the many factors that may affect processing and application of our product beyond our control, BGT Materials expressly disclaims all obligation and liability as to any results obtained or arising from any use of the product or reliance on such information. Neither do these data imply any warranty of certain properties, nor the suitability of the product for any particular purpose. The information provided herein relates only to the specific product designated and may not be applicable when such product is utilized in combination with other additives or in any process. The product should be stored in a cool, dry environment away from excess humidity, preferably in an inert atmosphere. Aggregation may occur.